

Splice Wash

Available in 1 gallon cans or 5 gallon pails Also available in Low VOC formula

Product Information

Splice Wash is a clear solvent used to clean dirt and containments from single ply roof systems. Especially used on old membranes to remove dirt prior to application of tape primers or seam adhesives. Change rags or applicator pads frequently! Do not allow product to puddle on EPDM for long periods of time. Discarded rags should be disposed of properly and will be a flammable hazard. No smoking or open flames on the roof while using this product. Also available in a Low VOC formula for use in OTC states.

Application Instructions:

The use of LionGUARDTM Toluene Splice Wash prior to application of this product is recommended. This product should be scrubbed into the EPDM surface thoroughly to remove surface debris. Change applicator pads frequently and cover an area in excess of the area to be seamed. No special applicator is required. When used with clean TPO, this primer is a cleaner and primer and the use of Toluene Splice Wash is not required. Solvent resistant gloves should be used when applying this product.

Physical Properties:

Color: Clear Viscosity (eps): Water thin

Density (#/**GAL.**): 7.23# % **Solids**: 0

Flash Point (F): 41F TCC

Solvent System: Aromatic

Base: Aromatic solvent

Clean-up Solvent: N/A

Storage: May be stored outside if protected from water. **Packaging:** 1 gallon (6 gal/cs) or 5 gallon pail

Hazards: Extremely flammable. Avoid repeated skin contact or the breathing of concentrated vapors. Use in well ventilated areas away from heat, sparks, fire, flame and ignition sources. Vapors are heavier than air and may travel a considerable distance to an ignition source and flash back. Do not inhale vapors above TLV as listed on the SDS.

Freight Classification: UN1133, ADHESIVE, 3 PGII NMFC# 170060 CLASS 55

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

User's Responsibility

This Product Information cannot cover all possible situations, which the user may experience during processing. Each aspect of your operations should be examined to determine if, or where, additional precautions may me necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without warranty, express or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained form the use thereof. Compliance with all applicable