



Made exclusively for NEMEON Members by APOC

PROFESSIONAL-GRADE PRODUCTS

LionGUARD #15 Roofing Felt (ASTM D4869 TYPE 1)

PRODUCT DESCRIPTION

LionGUARD asphalt saturated felts are made from virgin and recycled wood pulp that is saturated with a premium asphalt. The saturation of the organic felt mat promotes a greater resistance to vapor transmission, a heavier sheet, greater tensile strength, and more resistance to tear when being installed.

USES

LionGUARD organic felts are excellent underlayments for steep-slope roofing such as 3-tab shingles, wood shakes, and tiles. In addition, these felts can be installed under all types of building materials, flooring, and siding including stucco, aluminum, vinyl, and wood. LionGUARD organic felts are excellent secondary protection barriers against wind, moisture, and other environmental elements.

PRODUCT SPECIFICATIONS

TYPICAL TEST CRITERIA FOR ASTM D4869 TYPE 1 FELTS

| | |
|--|-----|
| Roll width, minimum inches | 36 |
| Area of roll, minimum sf | 432 |
| Net mass saturated felt, min lb/100 sf | 8 |
| Mass of saturant, minimum lb/100 sf | 4 |
| Mass of desaturant felt, min lb/100 sf | 4 |
| Ash, maximum percent | 10 |
| | |
| Pounds Roll Weight | 37 |
| Rolls per Pallet | 36 |
| | |
| | |
| | |
| | |

NEMEON, Inc. | 6043 Hudson Rd. Suite 350 Woodbury, MN 55125
Phone: (651) 788-7810 Fax: (651) 788-7807 | www.nemeon.com

APOC | 5903 Paramount Blvd, Long Beach, CA 90805
Phone: 1-800-562-5669 | www.apoc.com

