

LionGUARD ASPHALT PRIMER



PRODUCT DESCRIPTION

LionGuard Asphalt Primer is a general-purpose asphalt primer for preparing surfaces prior to the application of hot or cold applied asphalt coatings and cements. Ideal for use on dried out built-up asphalt roof surfaces, concrete, masonry, gypsum, brick and metal surfaces. Meets ASTM D-41.

ADVANTAGES

- » *Binds up dust and dirt*
- » *Improves bond of cements and coatings*
- » *Provides a firm base*

INSTALLATION

All surfaces to be coated must be dry, clean and free from oil, grease, debris and loose coating. Apply evenly to the surface by roof brush or airless spray equipment at the rate of 0.5 to 1 gallon per 100 sq.ft. Coverage will vary depending on the texture and porosity of the surface.

CLEAN UP & STORAGE

Clean tools and equipment with mineral spirits or similar solvent. Use caution when handling combustible materials. Store in a dry area where the temperature is between 50°F and 100°F.

PACKAGING



5 Gallon



Spray Can

CAUTION COMBUSTIBLE

Do not use near open flame or fire. Avoid breathing solvent fumes and prolonged contact with skin. Do not use in a confined space. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Do not thin. Keep container closed when not in use. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.