

LionGUARD FLASHING CEMENT



PRODUCT DESCRIPTION

LionGuard Flashing Cement is a multi-purpose asphalt mastic comprised of refined asphalts and solvents along with asbestos-free fibers which blended together produce a compound of trowel grade consistency. LionGuard Flashing Cement can be used to make general repairs to seal flashings on asphalt roofs, metal roofs, concrete, masonry, brick and repairs to shingle roofs. Also good for repairing flashings on walls, chimneys, skylights and other general-purpose repairs. May be used to make emergency repairs on wet surfaces. Meets ASTM D-4586 Type I and ASTM D-3409. For use on wet or dry surfaces.

ADVANTAGES

- » *Easy to spread trowel consistency*
- » *Tough, durable cured film*
- » *Won't sag on vertical applications*

INSTALLATION

All surfaces should be clean and free of dirt, oil, grease and debris. Remove excess water if possible. Apply with a trowel or putty knife to an average thickness of 1/8" (8 gallons per 100 square feet). Press firmly into cracks and joints when making repairs. For best protection, embed either asphalt cotton or fiberglass reinforcing fabric between two applications over the area to repair.

CLEAN UP & STORAGE

Clean tools and equipment with mineral spirits or similar solvent. Use caution when handling combustible materials. Store in a dry area where the temperature is between 50°F and 100°F.

PACKAGING



3 Gallon



5 Gallon

CAUTION: COMBUSTIBLE

Do not use near open flame or fire. Avoid breathing solvent fumes and prolonged contact with skin. Do not use in a confined space. Do not take internally. If swallowed, do not induce vomiting. Call a physician immediately. Keep out of reach of children. Do not thin. Keep container closed when not in use. Dispose of in an environmentally safe manner. Cover air intake during application while drying.