

# LionGUARD WHITE ACRYLIC COATING



## PRODUCT DESCRIPTION

LionGuard White Acrylic Coating is a white acrylic elastomeric coating for use over smooth BUR roof surfaces that have aged 90-180 days and smooth and granular modified bitumen membranes that have aged 45 days. Also may be used to coat vertical surfaces such as concrete, CMU, brick, stucco, metal and wood. Concrete surfaces must be allowed to cure a minimum of 30 days before coating. This coating offers good reflective properties and durability to protect the underlying roof surface.

## ADVANTAGES

- » Bright white reflective coatings
- » Elastomeric - expands and contracts with the roof surface
- » Good asphalt stain resistance

## INSTALLATION

All surfaces must be dry, clean and free from dirt, dust and debris. All leaks and defects should be repaired with appropriate materials prior to coating. Apply in a two coat applications in order to provide the proper protection and receive the greatest benefit from the coating. Apply each coat at the rate of 1.5 gallons per 100 square feet per coat for a total coverage of 3 gallons per 100 square feet. Apply when temperatures are between 50°F and 100°F. Coverage rates may vary depending on the irregularity of the surface.

## CARE OF TOOLS

While coating is wet tools and equipment may be cleaned with soapy water. If coating is dry use mineral spirits or similar solvent, taking necessary precautions when handling flammable materials.

## CAUTION

Do not apply when rain is expected within 24 hours after application. Coating must be dried before exposure to water. Store in a heated room and keep container covered when not in use. Do not thin. Keep out of reach of children. Avoid prolonged contact with skin. Dispose of in an environmentally safe manner. Cover air intakes during application and while drying.

## PACKAGING



**5 Gallon**